

COLOUR

Natural Anodised, Dulux Powdercoat (black and white powdercoat available in matt and gloss finishes)

DIFFUSER OPTIONS

Clear, Ice & Opal Acrylic, Parabolic Louvre (non LED)

REFLECTOR

Alanod MIRO4 Digitally Designed & CNC Pressed Reflector System for both LED & Fluorescent

FLUORESCENT LAMP OPTIONS

Single Lamps - T5, T8
Twin Lamps - T5
Continuous Overlapping - T5
Continuous End-to-End - T5, T8
Asymmetric - T5, T8

LED LAMP OPTIONS

650lm Philips Fortimo 4.6w ZHAGA LED Boards 1100lm Philips Fortimo 8.1w ZHAGA LED Boards SuperFLEX 15w LED Strip (all LEDs are CRI80+ and 3.5 SDCM Colour Consistency)

LIGHT DIRECTION

Direct, Indirect, Direct/Indirect

FLUORESCENT CONTROL GEAR

Osram, Tridonic or Phillips Control Gear (0-10v Dim, DSI Dim, DALI Dim)

LED CONTROL GEAR

Philips XITANIUM LED Drivers (Non-Dim or DALI Dim Options)

ENERGY EFFICIENCY

Fluorescent T5 Single Lamp - 88% LOR Clear Reeded Diffuser
Philips Fortimo LED Boards – up to 96 delivered lumens/watt with Ice Diffuser

TESTING DATA

IES LM-79, IES LM-80 for Philips LEDs and NATA Approved Photometrics for fluorescents.

MOUNTING OPTIONS

Rod Suspended, Wire Suspended, Wall Mounted, Surface Mounted

BENDS

45°, 90°, Custom

WEIGHT

2.6 kg/mtr

ACCESSORIES

Available with Wall Mounting Extrusion Screwless End Cap, Philips LED On-Board EMG, LED Spitfire, LED Downlights, IP54 Gasketted.













140 D





Ph: 0433 490 844 E: sales@catalinalighting.com.au W: www.catalinalighting.com.au

102 mm